



Fibre Optic Splice Closure



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com

Fibre Optic Inline Closure C.05.JC-L.F01

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fibre optic joint closure is to protect the fibre joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 67 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 67 ratings.



Applications

- Underground
- Aerial

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

Features

- Compacted design suitable for FTTH application
- Hinge based structure
- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation.
- Inclusive of sheath conservation and central strength member fasten feature
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware
- RoHS compliance

Specifications

Part number	Dimension(mm)	Ports	Capacity	Material	Protection class
C.05.JC-L.F01	300 x 107 x 38	4 ports, each port for max diameter 10mm	12 splices	MPP	IP 67

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*