



Fibre Optic Patch Panel



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com

1U 24 Ports for LC SM DX Blank Fibre Termination Box

Drawer patterned fibre patch panels designed to have 12 to 48 ports. It is appropriate for telecommunications network, fibre networks and optical cable systems. This rack mount patch panel has a sliding design with four cable entries at the rear. A set of bayonets has been attached to the box to install the cabling. ABS material has been utilized to form the splice tray, which is accessible for 0.9 mm, 2.0 mm and 3.0 mm fibre cables. Each patch panel can accommodate splice trays, panels and cable management accessories.



Applications

- LAN/WAN
- CATV network
- FTTX
- Broadcasting

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

Features

- Exceptional design with matte powder-coated exterior
- Blank fibre termination box is suitable for LC SC ST adapter; 3x different adapters panels
- Unit is 19" mountable
- Front cable tray for easy fibre management
- LC/SC/ST panels consist of accessories, which can be used basis the user requirement
- 4 cable entries into the patch panel

Specifications & Technical Parameters

Adapters, pigtails, splice trays and splice sleeves are not included

| | |
|------------------------------|--|
| Material | Steel and ABS plastic |
| Cassette (splices trays) | 1-cassette to hold 12 splices |
| Cable input | 4 cable entry ports |
| Adapters | Accessible for the installation of LC/FC/SC/ST/other adapters |
| Working temperature | -40°C~ + 60°C |
| Design | TIA/EIA568.C, ISO/IEC 11801, En50173, IEC60304, IEC61754, EN-297-1 |
| Colour | Matte black |
| Curvature radius | ≥40mm |
| Lateral pressure- resistance | 500N |
| Resistance | 750N |

Product Description

| | |
|--------------|-------------------------|
| Part number | C.08.FPP.1 Block Custom |
| Dimensions | L 483*W 350*H 44.5 |
| Installation | 19" rack mountable |
| Port | 24 for LC SM DX |
| Materials | SPCC |

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*