



CAT6 UTP Patch Cord



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com

CAT6 UTP Patch Cord

WEBB CAT6 unscreened UTP patch cords are designed to meet and exceed ANSI/TIA/EIA 568B standards. WEBB patch cords are made by high-quality patch cable and RJ45 modular plug. These cables are simple, cost effective, reliable provides high speed transmission of data.

Features

- 250 MHz with over 2.5Gbps
- 4 pairs unshielded twisted pair cable
- RJ45 Connectors - Flash gold plated
- Durable for 750 insertion cycles
- Available in LSZH, PVC, PE sheaths
- Available in different lengths
- Available in different colors

Applications

- Data centre and telecommunication networks
- LAN applications
- CATV - cable television, CCTV

Technical Specifications

Conductor	24AWG
Operating life	750 Insertion cycle
Dielectric pair	4 pairs
Conductor material	Copper
Contact material	Phosphor bronze
Contact plating	60μ gold
Overall diameter	5.1±0.05mm
Connector	RJ45
Temperature range	-30°C to +75°C
Cabling standard	EIA/TIA 568B
Flame retardance, smoke emission	IEC 60332-1, IEC 61034
Typical applications	IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

PATCH CORDS PART NUMBER KEY

Part Number: C.04.C6.UT._ _._ _

C.04.Cable.Cable Construction.Length.Sheath.Color

Please add the codes from the tables below in the above format to derive your desired product part number

Cable	Code
CAT6	C6

Cable Construction	Code
UTP	UT

Length	Code
1 meter	01
2 meter	02
3 meter	03
5 meter	05
Custom	C

Sheath	Code
PVC	P
LZOH	L

Color	Code
Grey	G
Black	B
Red	R
Blue	U
Yellow	Y
Orange	O

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*